

Automated Photo Capture Stand

The `derbynet-extras` package includes some scripts to support using a Raspberry Pi and a barcode scanner to drive an automated photo capture stand. (See it in action on [YouTube](#).) The `photostand.sh` script triggers the camera when a barcode is scanned, and uploads the photo and assigns it to a racer.

This document describes setting up such a photo capture station¹.

1. Gather your hardware:
 - (a) A Raspberry Pi running Raspberry Pi OS (previously called Raspbian).
 - (b) A barcode scanner
 - (c) A camera, one of:
 - i. A webcam; *OR*
 - ii. A digital SLR camera and USB cable; *OR*
 - iii. A Canon camera running the “Canon Hack Development Kit” (<https://chdk.fandom.com/wiki/CHDK>)
2. Install the `derbynet-extras` package on the Raspberry Pi (see the “Installation- Debian” document for details).
3. Install software to interact with your camera.
 - (a) If using a webcam, install `fswebcam`:

```
sudo apt install -y fswebcam
```
 - (b) If using a dSLR, install `gphoto2`:

```
sudo apt install -y gphoto2
```
 - (c) If using CHDK, install the `chdk` picture transfer protocol (`chdkptp`):
 - i. Download `chdkptp` from <https://app.assembla.com/spaces/chdkptp/documents>. (As of this writing, `chdkptp-r964-raspbian-gui.zip` is the most recent version for Raspberry Pi OS.)
 - ii. Unzip the contents into `/opt/chdkptp` directory.
 - iii. Install LibUSB:

```
sudo apt install -y libusb-0.1-4
```
 - iv. Make the `chdkptp` script available as a command:

¹ The `shoot-then-scan.sh` script is similar to `photostand.sh`, but allows the operator to take a picture manually, and *then* scan a barcode to upload the photo and assign it to a racer. (Better than trying to capture a smile by scanning a barcode.)

```
sudo ln -s /opt/chdkptp/chdkptp.sh /usr/local/bin/chdkptp
```

(This *must* be a symbolic link, as the script needs to find other files near it.)

4. *Optional but recommended:* If you intend to run “headless,” (i.e., without the clutter of a keyboard and monitor), it’s useful to connect a speaker to the audio-out jack, and install command line tools for speech synthesis and sound effects to help you understand what the pi is doing:

```
sudo apt install -y flite mpg123
```

(Bringing a keyboard and monitor for on-site troubleshooting is still recommended, even if you hope not to have to use them.)

5. Copy the autostart file into place:

```
mkdir .config/autostart
cp /usr/share/derbynet/autostart/photostand.desktop .config/autostart/
```

6. Edit /etc/derbynet.conf

- (a) Indicate which photo capture software you’re using by uncommenting (removing the leading ‘#’ character from) *one* of these three lines:

```
# PHOTO_CAPTURE=gphoto2    # default
# PHOTO_CAPTURE=chdkptp
# PHOTO_CAPTURE=fswebcam
```

- (b) Indicate whether you’re capturing photos of cars or of racers (heads) by uncommenting one of these two lines:

```
# PHOTO_REPO=head
# PHOTO_REPO=car
```

- (c) If you wish, you can have the script check in a racer when the racer’s bar code is scanned. Include this line to enable that feature:

```
PHOTO_CHECKIN=1
```

- (d) If you really want to get fancy, /etc/derbynet.conf can also include some bash script overrides of functions in photostand.sh and the library files it includes. For example, this function auto-zooms a particular camera using CHDK for a particular photo geometry (YMMV):

```
# Auto-zoom the chdkptp camera for car photo station
unset prepare_camera_before_shot
prepare_camera_before_shot() {
    chdkptp -c -e"rec" -e"lua set_zoom(40)"
}
```